

TECHNICAL DATA SHEET

11/25/2009

NONIVAMIDE IN BENZYL ALCOHOL, 10% WT.				
Formula: Unspecified	FW:	Kosher: <input checked="" type="checkbox"/>	FCC: <input type="checkbox"/>	
Appearance and Color: } Liquid / Pale yellow to orange	Part Code: 13136			
Density (g/ml) d_4^{20} = NA	RI: n_D^{25} = NA	Soluble in: Code: FS=Freely, SpS=Sparingly, VSI=Very Slightly, I=Insoluble		
Flash Point: 96°C Method: Closed Cup	Boiling Point:	<input checked="" type="checkbox"/> Alcohol		
Vapor Press: mm Hg, 20°C log K(ow):	Acid Number: ≤ NA	<input type="checkbox"/> Propylene Glycol		
		<input type="checkbox"/> Essential Oils		
		<input checked="" type="checkbox"/> Water		
CHROMATOGRAPHIC ANALYSIS Purity: ≥ 10% - 12%				
GC: 0.53 mm ID x 30 m length, ~ 4.5 ml/min He Carrier Gas. FID DB5: 100° (2' hold) to 225°@ 50°/min (90' hold)				
REFERENCE NUMBERS		Natural/Nature Identical/Artificial: <input type="checkbox"/>	ODOR/TASTE	
FEMA/GRAS N°: Co. Europe N°: C.A.S. N°: EINECS N°: TARIFF N°: 2924.29.9500		NATURAL OCCURRENCE		/
TRANSPORT:				
Hazard: Miscellaneous	REGULATION	HAZ. CLASS	PG	UN N°
Point 1 2 4	1 R.T.M.D.			
Not Regulated	2 ADR/RID			
<u>Category / other info:</u>	3 I.A.T.A.	9	-	3334
	4 I.M.D.G.			
SAFETY DATA: Available	TSCA:	PACKING CONTAINERS:		
STORAGE: Under Nitrogen	Temperature: ≤ -18°C <input type="checkbox"/>	<input type="checkbox"/> Epoxy-coated Steel Drums		
	≤ 5°C <input type="checkbox"/>	<input type="checkbox"/> Stainless Steel Drums		
Shelf Life: ~ 24 months	RT <input checked="" type="checkbox"/>	<input type="checkbox"/> Aluminum Bottles		
		<input checked="" type="checkbox"/> Glass Bottles		
		<input checked="" type="checkbox"/> Plastic / Plastic-lined drums		

Unless otherwise noted, this data sheet is for your information only and Fontarôme Chemical cannot be held responsible for its contents.