

TECHNICAL DATA SHEET

11/25/2009

WS-5					
Formula: C15 H27 NO3	FW: 269.38	Kosher: <input type="checkbox"/>		FCC: <input type="checkbox"/>	
Appearance and Color: } Crystalline Powder / White	Part Code: 13919				
Density (g/ml) d_4^{20} = NA	RI: n_D^{25} = NA	Soluble in: Code: FS=Freely, SpS=Sparingly, VSI=Very Slightly, I=Insoluble			
Flash Point: 100°C Method: Closed Cup	Melting Point: 80°-82°C	<input type="checkbox"/> FS Alcohol			
Vapor Press: mm Hg, 20°C log K(ow):	Acid Number: ≤ NA	<input type="checkbox"/> FS Propylene Glycol			
		<input type="checkbox"/> FS Essential Oils			
		<input type="checkbox"/> I Water			
CHROMATOGRAPHIC ANALYSIS Purity: ≥ 98.0% GC: 0.53 mm ID x 30 m length, ~ 4.5 ml/min He Carrier Gas. FID DB-5: 100°C (0 min HOLD) to 225°C at 10°C/min (20 min HOLD)					
REFERENCE NUMBERS FEMA/GRAS N°: 4309 Co. Europe N°: C.A.S. N°: 68489-14-5 EINECS N°: TARIFF N°: 2924.29.9500		Natural/Nature Identical/Artificial: <input type="checkbox"/> NATURAL OCCURRENCE			ODOR/TASTE Faintly mentholic, extremely cooling /
TRANSPORT:					
Hazard:	REGULATION	HAZ. CLASS	PG	UN N°	
Point 1 2 3 4	1 R.T.M.D.				
Not Regulated	2 ADR/RID				
Category / other info:	3 I.A.T.A.				
	4 I.M.D.G.				
SAFETY DATA: Available	TSCA:	PACKING CONTAINERS:			
STORAGE: Under Nitrogen	Temperature: ≤ -18°C <input type="checkbox"/>	<input checked="" type="checkbox"/> Epoxy-coated Steel Drums			
	≤ 5°C <input type="checkbox"/>	<input type="checkbox"/> Stainless Steel Drums			
Shelf Life: ~ 12 MONTHS	RT <input checked="" type="checkbox"/>	<input type="checkbox"/> Aluminum Bottles			
		<input checked="" type="checkbox"/> Glass Bottles			
		<input checked="" type="checkbox"/> Plastic / Plastic-lined drums			

Unless otherwise noted, this data sheet is for your information only and Fontarôme Chemical cannot be held responsible for its contents.